

8-Port Console Server with Built-In Modem, Dual GbE NIC, 4Gb Flash and Dual SFP

MODEL NUMBER: **B093-008-2E4U-M**



Rack console for remotely accessing and controlling serial-based networking equipment through one highly secure gateway.

Features

Access All Your Serial and Network Devices from Anywhere in the WorldThe B093-008-2E4U-M 8-port console server provides secure in-band (primary network) and out-of-band (alternate channel) remote access to serial- and network-connected routers, network switches, firewalls, PBX systems, UPS systems, PDUs and other devices. It offers reliable network connectivity with dual Gigabit primary and failover Ethernet ports for redundancy. You can use it in a wide variety of applications, including wiring closets, branch offices, point-of-sale and other remote sites where quick resolution of network issues is imperative.

Simple and Flexible AccessibilityEight serial RS-232 console ports are configured to use standard Cat5e/6 patch cable when connecting to Cisco devices. They integrate with industry-standard directory servers using TACACS+, RADIUS, LDAP and Kerberos authentication. Provides 4Gb of internal NAND flash memory.

Built-In PSTN Modem for Out-of-Band AccessA V.92 serial data/fax modem enables out-of-band (alternate channel) access when remote sites experience a network outage. You can dial into the rack console from anywhere at any time, eliminating the costly need for additional USB modems that can be accidentally disconnected or have compatibility issues.

Router/GatewayEach gateway can port forward to an unlimited number of locally networked hosts (computers, routers). This rack console also includes a built-in stateful firewall and embedded DHCP server to host a separate management LAN for critical traffic.

The Utmost in Security to Keep Your Sensitive Data PrivateThe B093-008-2E4U-M supports the following security features and standards: PCI DSS 3.2, FIPS 140-2, SSL and SSH, stateful firewall, OpenVPN and IPSec VPN support. The embedded FIPS 140-2 OpenSSL cryptographic module is validated to meet FIPS 140-2 standards and has received Certificate #2473.

PowerMan PDU and UPS SupportThis 8-port console server uses PowerMan for PDU and RPC management and Network UPS Tools for UPS system monitoring and management. It provides support for Tripp Lite and other power products, so you can remotely manage power to your connected equipment.

USB Console and Digital I/O (DIO) PortsFour USB 2.0 console ports allow connection to newer devices with USB console ports, such as Tripp Lite's wide variety of PDUs and UPS systems with WEBCARDLX and LX Platform remote management cards. Two DIO ports are included for connecting compatible devices, such as drive relays and alarms.

Compact Design for Convenient MountingThe heavy-duty steel housing comes with mounting brackets for easy installation in an EIA-standard 19-inch rack. Its fanless form factor also allows desktop deployment on four included rubber feet that help prevent the unit from sliding.

TAA-Compliant for GSA Schedule PurchasesThis serial console server is compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

4-Year Warranty and Environmentally Responsible DesignThe B093-008-2E4U-M comes with a 4-

Highlights

- Manage routers, UPS systems and other serial-based equipment from anywhere at any time 24/7
- Built-in V.92 serial data/fax modem provides out-of-band remote access
- Dual Gigabit Ethernet ports for primary network connection and automatic failover
- Designed for standard Cat5e/6 patch cable when connecting to Cisco devices
- Easy installation on desktop or 19 in. racks using included mounting hardware

Applications

- Securely access and control servers, routers, KVM switches and other serial-connected devices in your data center 24/7
- Manage diverse server and device platforms using a network connection
- Oversee IT infrastructure remotely via network
- Troubleshoot equipment issues without spending time/money traveling to remote locations

Package Includes

- B093-008-2E4U-M 8-Port Serial Console Server with Built-In Modem, Dual GbE NIC, 4Gb Flash and Dual SFP
- Terminal block
- DB9F to RJ45 crossover serial



year warranty. It's manufactured in compliance with strict RoHS specifications, reflecting Tripp Lite's commitment to environmental responsibility.

adapter

- External power supply w/4 ft. cord (Input: 100–240V, 50/60 Hz, 0.4A; Output: 12V 1.25A)
- (4) International plug adapters (North America, Europe, U.K., Australia)
- Rack-mounting hardware
- (4) Rubber feet
- Quick Start Guide

Specifications

| OVERVIEW | |
|--|--|
| UPC Code | 037332209283 |
| Multi-User | Yes |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 127; 200; 208; 220; 230; 240 |
| External Power Supply Input Specs (V / Hz / A) | 100-240V/ 50/60Hz / 0.4A |
| External Power Supply Output Specs (V / A) | 12V / 1.25A |
| External Power Supply Cord Length (ft.) | 4.0 |
| External Power Supply Cord Length (m.) | 1.2 |
| External Power Supply Plug(s) | NEMA 1-15P North America; CEE 7/16 Schuko; BS 1363 UK; AS/NZS 3112 Australia |
| External Power Supply Certifications | CE; FCC; UL; cUL; TUV; PSE; C-Tick; GS; RoHS; CB |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | 7 LED's for Power, Heartbeat-Firmware Running, Serial Connectivity and Network Ports |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Metal |
| Rackmountable | Yes |
| Shipping Dimensions (hwd / cm) | 10.67 x 17.78 x 23.62 |



| | |
|--------------------------------------|---|
| Shipping Dimensions (hwd / in.) | 4.20 x 7.00 x 9.30 |
| Shipping Weight (kg) | 1.18 |
| Shipping Weight (lbs.) | 2.60 |
| Unit Dimensions (hwd / cm) | 3.556 x 16.51 x 10.16 |
| Unit Dimensions (hwd / in.) | 1.4 x 5.1 x 4.7 |
| Unit Packaging Type | Box |
| Unit Weight (kg) | 0.59 |
| Unit Weight (lbs.) | 1.30 |
| ENVIRONMENTAL | |
| Operating Temperature Range | -13 to 140 F (-25 to 60 C) |
| Storage Temperature Range | -40 to 167 F (-40 to 75 C) |
| Relative Humidity | 5% to 90% RH, Non-Condensing |
| BTUs | 39.2 BTU/Hr |
| Power Consumption (Watts) | 11.5 |
| COMMUNICATIONS | |
| IP Remote Access | Yes |
| Network Speed | 1Gbps |
| IEEE Standards Supported | 802.3; 802.3ab; 802.3ad |
| CONNECTIONS | |
| Ports | 8 |
| Side A - Connector 1 | RJ11 (FEMALE); (2) RJ45 (FEMALE); (2) SFP+ (FEMALE) |
| Side B - Connector 1 | (8) RJ45 (FEMALE); (4) USB A (FEMALE) |
| FEATURES & SPECIFICATIONS | |
| Port Selection | GUI |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| Driver Required | No |
| Authentication Supported | RADIUS; LDAP; TACACS |
| Common Access Card (CAC) Support | No |
| Technology | Modem; SFP+/QSFP+/QSFP28; Serial (RS232) |
| REMOTE ACCESS | |
| Modem Port | Yes |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| CERTIFICATIONS | |
|-------------------------------------|---|
| Certifications | Tested to CE, FCC, UL, TUV, C-Tick, RoHS, REACH |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 4-year limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>